## **SAFETY DATA SHEET**

Print Date: 04/23/2025 Revision Date: 04/23/2025

\_\_\_\_\_

#### 1. IDENTIFICATION

Product Description	RAL 5022 – Night Blue - Matte
Trade Name	TGIC
Product #	RAL5022MATTE
Supplier	Columbia Coatings
	1173 Industrial Park Rd
	Columbia, TN 38401
Contact	(931) 388-7730 Phone
	(931) 388-5573 Fax

## 2. HAZARD IDENTIFICATION

Product is a mixture of hazardous and non-hazardous ingredients compounded in a polymer.

*Information pertaining to particular		
danger for man and environment.		
-Harmful by inhalation and for if swallows		

-Harmful by inhalation and/or if swallowed.



# \*Classification System

-Classification was made according to the latest editions of international substances lists, and expanded upon from company literature data.

NFPA Ratings	Scale 0-4
Health	1
Fire	1
Reactivity	0

HMIS Ratings	Scale 0-4
Health	1
Fire	1
Reactivity	0

3. Composition/information on ingredients

Hazardous	Case#	TLV-ACGIH	PEL-OSHA	CONCENTRATE
Components				%
barium sulfate	7727-43-7	5 mg/m <sup>3</sup>	5 mg/m <sup>3</sup>	10-20
titanium dioxide	13463-67-7	2.5 mg/m <sup>3</sup>	15 mg/m <sup>3</sup>	<1
1,3-Benzenedicarboxylic	26811-89-2	10 mg/m <sup>3</sup>	15 mg/m <sup>3</sup>	50-75
acid, polymer with 2,2-				
dimethyl-1,3-propanediol				
1,3,5-tris(oxiranylmethyl)-	2451-62-9	$0.05 \text{ mg/m}^3$	n/a	1-5
1,3,5-triazine-				
2,4,6(1H,3H,5H)-trione				

#### 4. FIRST AID MEASURES

#### \*After Inhalation

-Supply fresh air and seek medical attention.

#### \*After Skin Contact

-Generally the product does not irritate the skin but water and soap can be used for rinsing.

## \*After Eye Contact

-Rinse opened eye for several minutes under clean running water.

## \*After Swallowing

-Rinse mouth out and then drink water. If symptoms persist, seek medical attention.

## 5. FIRE FIGHTING MEASURES

## \*Suitable Extinguishing Agents

-Use CO2, extinguishing powder or water spray. Fight larger fires with water spray, alcohol, or resistant foam.

## \*Firefighting Instructions

-Use fully protective equipment with self-contained breathing apparatus.

## \*Explosion

-Avoid generating dust; fine dust dispersed in the air in sufficient concentrations, and in the presence of an ignition source is a potential dust explosion hazard.

## \*Personal Protective Equipment

-Wear self-contained respiratory device.

#### 6. ACCIDENTAL RELEASE MEASURES

## \*Personal Related Safety Precautions

-Ensure adequate ventilation

## \*Measure for Environmental Protection

-Do not allow to enter sewer/surface or ground water.

## \*Measure for Cleaning and Collecting

-Pick up mechanically. Dispose contaminated material as waste according to item 13.

#### 7. HANDLING AND STORAGE

#### \*Information For Safe Handling

-Prevent formation of dust and ensure good ventilation/exhaustion at the workplace.

## \*Information About Protection Against Explosions and Fires

-Dust can combine with air in suspended form when applying and can be an explosive mixture.

## \*Requirements To Be Met By Storerooms and Receptacles

-Store in a cool, dry place in a tightly closed container. Storage temperatures not to exceed 25°C/77°F to ensure product quality. Shelf life of the product at that temperature is up to 2 years, after that, the performance of the products will deteriorate. Protect from heat and direct sunlight. Protect from humidity and water.

## \*Information About Storage In Once Common Storage Facility.

-Not Required

Print Date: 04/23/2025
8. EXPOSURE CONTROLS AND PERSONAL PROTECTION Revision Date: 04/23/2025

*Additional Information About Design of Technical Systems	
-No Data: See item 7.	
*Components with Limited Values That May Require Monitoring at the Workplace.	
-See product ingredients.	
*Personal Protective Equipment	
-Keep away from foods, beverages, animals and feed. Wash hands before breaks and at the end	
of work. The usual precautionary measures for handling chemicals should be followed.	

Protective Equipment for	It is recommended to use MSHA approved respirator when
Inhalation	handling powders. Powders are considered nuisance dust.
Hygienic Measures for	Avoid skin contact; use long sleeve shirts and impermeable gloves
Skin Contact	at a minimum when handling powders. TYVEK full body suits or
	equivalent are recommended for heavy exposure. Be sure to
	launder contaminated clothing before reuse. Wash skin with mild
	soap and water if contact occurs. If symptoms continue seek
	medical attention.
Eye Protection	Require the use of safety goggles with side shields. Powder
	particles can be abrasive on the cornea. In case of eye contact,
	flush with plenty of fresh water. If irritation develops or persists,
	seek medical attention.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Form: Solid, finely divided powder  Color: According to product specs  Odor: n/a  Chemical  Specific Gravity: Approx. 1.55 g/cm³  Coverage: 124 sq. ft/lb. @ 1 mil  Flash Point: n/a  Hardness: 2H (ASTM D3363)  Danger of Explosion: n/a  Density: 1.47 g/cm³  Solubility with Water: Insoluble  Solvent Content: n/a  Salt Spray: 1000 Hrs. Pass <1/8" Scribe Creep - No Blisters (ASTM B117)  Film Thickness: 2.5- 3.5 mils  Humidity: 1000 Hrs. Pass <1/16" Scribe Creep - No Blisters (ASTM D-1735)  Flexibility: 1/8" (ASTM D522)  Impact: 100 in-lb. direct & reverse  Cross Hatch Adhesion: 5B (ASTM D3359)	9. PHISICAL AND CHEMI	9. PHYSICAL AND CHEMICAL PROPERTIES	
Color: According to product specs Odor: n/a  Chemical  Specific Gravity: Approx. 1.55 g/cm³  Coverage: 124 sq. ft/lb. @ 1 mil  Flash Point: n/a  Hardness: 2H (ASTM D3363)  Danger of Explosion: n/a  Density: 1.47 g/cm³  Solubility with Water: Insoluble  Solvent Content: n/a  Salt Spray: 1000 Hrs. Pass <1/8" Scribe Creep - No Blisters (ASTM B117)  Film Thickness: 2.5-3.5 mils  Humidity: 1000 Hrs. Pass <1/16" Scribe Creep - No Blisters (ASTM D-1735)  Flexibility: 1/8" (ASTM D522)  Impact: 100 in-lb. direct & reverse	Physical		
Chemical  Specific Gravity: Approx. 1.55 g/cm³  Coverage: 124 sq. ft/lb. @ 1 mil  Flash Point: n/a  Hardness: 2H (ASTM D3363)  Danger of Explosion: n/a  Density: 1.47 g/cm³  Solubility with Water: Insoluble  Solvent Content: n/a  Salt Spray: 1000 Hrs. Pass <1/8" Scribe Creep - No Blisters (ASTM B117)  Film Thickness: 2.5- 3.5 mils  Humidity: 1000 Hrs. Pass <1/16" Scribe Creep - No Blisters (ASTM D-1735)  Flexibility: 1/8" (ASTM D522)  Impact: 100 in-lb. direct & reverse	Form:	Solid, finely divided powder	
Chemical  Specific Gravity: Approx. 1.55 g/cm³  Coverage: 124 sq. ft/lb. @ 1 mil  Flash Point: n/a  Hardness: 2H (ASTM D3363)  Danger of Explosion: n/a  Density: 1.47 g/cm³  Solubility with Water: Insoluble  Solvent Content: n/a  Salt Spray: 1000 Hrs. Pass <1/8" Scribe Creep - No Blisters (ASTM B117)  Film Thickness: 2.5- 3.5 mils  Humidity: 1000 Hrs. Pass <1/16" Scribe Creep - No Blisters (ASTM D-1735)  Flexibility: 1/8" (ASTM D522)  Impact: 100 in-lb. direct & reverse	Color:	According to product specs	
Specific Gravity: Approx. 1.55 g/cm³ Coverage: 124 sq. ft/lb. @ 1 mil Flash Point: n/a Hardness: 2H (ASTM D3363)  Danger of Explosion: n/a  Density: 1.47 g/cm³ Solubility with Water: Insoluble Solvent Content: n/a Salt Spray: 1000 Hrs. Pass <1/8" Scribe Creep - No Blisters (ASTM B117) Film Thickness: 2.5-3.5 mils Humidity: 1000 Hrs. Pass <1/16" Scribe Creep - No Blisters (ASTM D-1735) Flexibility: 1/8" (ASTM D522) Impact: 100 in-lb. direct & reverse	Odor:	n/a	
Coverage: 124 sq. ft/lb. @ 1 mil  Flash Point: n/a  Hardness: 2H (ASTM D3363)  Danger of Explosion: n/a  Density: 1.47 g/cm³  Solubility with Water: Insoluble  Solvent Content: n/a  Salt Spray: 1000 Hrs. Pass <1/8" Scribe Creep - No Blisters (ASTM B117)  Film Thickness: 2.5-3.5 mils  Humidity: 1000 Hrs. Pass <1/16" Scribe Creep - No Blisters (ASTM D-1735)  Flexibility: 1/8" (ASTM D522)  Impact: 100 in-lb. direct & reverse		Chemical	
Flash Point: Hardness: 2H (ASTM D3363)  Danger of Explosion:  n/a  Density: 1.47 g/cm³  Solubility with Water: Insoluble  Solvent Content: Aslt Spray: 1000 Hrs. Pass <1/8" Scribe Creep - No Blisters (ASTM B117)  Film Thickness: 2.5- 3.5 mils  Humidity: 1000 Hrs. Pass <1/16" Scribe Creep - No Blisters (ASTM D-1735)  Flexibility: 1/8" (ASTM D522)  Impact: 100 in-lb. direct & reverse	Specific Gravity:	Approx. 1.55 g/cm <sup>3</sup>	
Hardness: 2H (ASTM D3363)  Danger of Explosion: n/a  Density: 1.47 g/cm³ Solubility with Water: Insoluble Solvent Content: n/a Salt Spray: 1000 Hrs. Pass <1/8" Scribe Creep - No Blisters (ASTM B117) Film Thickness: 2.5-3.5 mils Humidity: 1000 Hrs. Pass <1/16" Scribe Creep - No Blisters (ASTM D-1735) Flexibility: 1/8" (ASTM D522) Impact: 100 in-lb. direct & reverse	Coverage:	124 sq. ft/lb. @ 1 mil	
Danger of Explosion: n/a  Density: 1.47 g/cm³ Solubility with Water: Insoluble Solvent Content: n/a Salt Spray: 1000 Hrs. Pass <1/8" Scribe Creep - No Blisters (ASTM B117) Film Thickness: 2.5- 3.5 mils Humidity: 1000 Hrs. Pass <1/16" Scribe Creep - No Blisters (ASTM D-1735) Flexibility: 1/8" (ASTM D522) Impact: 100 in-lb. direct & reverse	Flash Point:	n/a	
Density: 1.47 g/cm³  Solubility with Water: Insoluble  Solvent Content: n/a  Salt Spray: 1000 Hrs. Pass <1/8" Scribe Creep - No Blisters (ASTM B117)  Film Thickness: 2.5-3.5 mils  Humidity: 1000 Hrs. Pass <1/16" Scribe Creep - No Blisters (ASTM D-1735)  Flexibility: 1/8" (ASTM D522)  Impact: 100 in-lb. direct & reverse	Hardness:	2H (ASTM D3363)	
Density: 1.47 g/cm³  Solubility with Water: Insoluble  Solvent Content: n/a  Salt Spray: 1000 Hrs. Pass <1/8" Scribe Creep - No Blisters (ASTM B117)  Film Thickness: 2.5-3.5 mils  Humidity: 1000 Hrs. Pass <1/16" Scribe Creep - No Blisters (ASTM D-1735)  Flexibility: 1/8" (ASTM D522)  Impact: 100 in-lb. direct & reverse	D (F ) :		
Solubility with Water: Insoluble  Solvent Content: n/a  Salt Spray: 1000 Hrs. Pass <1/8" Scribe Creep - No Blisters (ASTM B117)  Film Thickness: 2.5- 3.5 mils  Humidity: 1000 Hrs. Pass <1/16" Scribe Creep - No Blisters (ASTM D-1735)  Flexibility: 1/8" (ASTM D522)  Impact: 100 in-lb. direct & reverse	Danger of Explosion:	n/a	
Solubility with Water: Insoluble  Solvent Content: n/a  Salt Spray: 1000 Hrs. Pass <1/8" Scribe Creep - No Blisters (ASTM B117)  Film Thickness: 2.5- 3.5 mils  Humidity: 1000 Hrs. Pass <1/16" Scribe Creep - No Blisters (ASTM D-1735)  Flexibility: 1/8" (ASTM D522)  Impact: 100 in-lb. direct & reverse			
Solvent Content:n/aSalt Spray:1000 Hrs. Pass <1/8" Scribe Creep - No Blisters (ASTM B117)	Density:	1.47 g/cm <sup>3</sup>	
Salt Spray: 1000 Hrs. Pass <1/8" Scribe Creep - No Blisters (ASTM B117)  Film Thickness: 2.5- 3.5 mils  Humidity: 1000 Hrs. Pass <1/16" Scribe Creep - No Blisters (ASTM D-1735)  Flexibility: 1/8" (ASTM D522)  Impact: 100 in-lb. direct & reverse	Solubility with Water:	Insoluble	
Film Thickness: 2.5–3.5 mils  Humidity: 1000 Hrs. Pass <1/16" Scribe Creep - No Blisters (ASTM D-1735)  Flexibility: 1/8" (ASTM D522)  Impact: 100 in-lb. direct & reverse	<b>Solvent Content:</b>	n/a	
Humidity: 1000 Hrs. Pass <1/16" Scribe Creep - No Blisters (ASTM D-1735)  Flexibility: 1/8" (ASTM D522)  Impact: 100 in-lb. direct & reverse	Salt Spray:	1000 Hrs. Pass <1/8" Scribe Creep - No Blisters (ASTM B117)	
Flexibility: 1/8" (ASTM D522) Impact: 100 in-lb. direct & reverse	Film Thickness:	2.5- 3.5 mils	
Impact: 100 in-lb. direct & reverse	Humidity:	1000 Hrs. Pass <1/16" Scribe Creep - No Blisters (ASTM D-1735)	
	Flexibility:	1/8" (ASTM D522)	
Cross Hatch Adhesion: 5B (ASTM D3359)	Impact:	100 in-lb. direct & reverse	
	<b>Cross Hatch Adhesion:</b>	5B (ASTM D3359)	

Print Date: 04/23/2025 Revision Date: 04/23/2025

## 10. STABILITY AND REACTIVITY

## \*Product Stability

-No decomposition if used according to specifications.

# \*Thermal Decomposition/Conditions To Be Avoided

-Decomposition at high temperatures may yield Carbon Dioxide, Carbon Monoxide, Nitrous Oxide and other hazardous gases.

## \*Dangerous Reactions

-N/A

# \*Dangerous Products of Decomposition

-N/A

## 11. TOXICOLOGICAL INFORMATION

## \*Primary Irritant Effect

- -On the skin Powder can be irritation through rubbing action, also has a drying effect.
- -In the eye Powder can be irritating through rubbing, can cause abrasion on the cornea.

## \*Sensitization

-Sensitization possible through skin contact.

# \*Additional Toxicological Information

-The product shows the following danger according to internally approved calculation methods for preparations: Harmful!

#### 12. ECOLOGICAL INFORMATION

## \*General Notes

-Water hazard class 1 (Self-Assessment): Slightly hazardous for water.

#### 13. DISPOSAL INFORMATION

#### \*Packaging

-Disposal must be made according to official regulations.

#### 14. TRANSPORTATION INFORMATION

## \*DOT Regulations

-Non-Hazardous / Non-Regulated

## \*Maritime Transportation IMDG

-Non-Polluting

Print Date: 04/23/2025 Revision Date: 04/23/2025

## 15. REGULATIONS

## \*Product Related Hazard Information

-The product has been classified and marked in accordance with directives on hazardous materials.

## \*Hazard Symbols

-Harmful

# \*Hazard-Determining Components of Labeling

-TGIC

## \*Risk Phrases

- -Harmful by inhalation and if swallowed.
- -May cause sensitization by skin contact.

## \*Safety Phrases

- -Keep out of reach of children.
- -Keep container dry.
- -Keep container in a well-ventilated area.
- -Keep away from food, drink and animals/feed.
- -Do not breath gas/fumes/vapors/spray.
- -If swallowed, seek medical advice immediately and show this label.

## **16. OTHER INFORMATION**

THIS INFORMATION IS BASED ON OUR PRESENT KNOWLEDGE. HOWEVER, THIS DOES NOT CONSTITUTE A GUARANTEE FOR ANY SPECIFIC PRODUCT FEATURES AND SHALL NOT ESTABLISH A LEGALLY VALID CONTRACTUAL RELATIONSHIP.

Print Date: 04/23/2025 Revision Date: 04/23/2025